

| | |
|--------------------|---|
| DIMENSIONS | 6030mm x 1870mm x 2650mm |
| BODY | Fiberglass + ABS |
| ROOF | Solar Panels + Fiberglass |
| CHASSIS | High Strength Steel |
| WHEEL BASE | 2995mm |
| WHEEL TRACK | 1530mm (front) / 1560mm (rear) |
| TIRE SIZE | 225/70R15C |
| GROUND CLEARANCE | 125mm (full load) |
| SUSPENSION | Longitudinal Leaf Springs (rear) |
| STEERING | Hydraulic power assisted |
| TURNING RADIUS | 8.5m |
| BRAKE TYPE | 4 wheel hydraulic brakes with vacuum assistance |
| BREAKING DISTANCE | 7m |
| PASSENGER CAPACITY | 20 seated + 9 standing |
| CURB WEIGHT | 2900 kg |
| LOAD CAPACITY | 2.7 tons |
| CUMMING CAPACITY | 13% |
| ACCELERATOR | Resistive 0-5K |
| AC CONTROLLER | 72V / 550A |
| DC CONVERTER | 4 x 12V / 30A + 12V / 50A |
| CHARGING TIME | 10%/h |
| CHARGER | 2 units 72V / 20A GP EP3 PLUG |